



Suction Pump with Stainless Steel Box IP 68

Product Images



Short Description

Electrical pump for removing water out of decontamination showers for example, suitable for continuous operation. It can deliver fresh water as well as waste water with a maximum solid size of 0.11 in.

Description

Electrical pump for removing water out of decontamination showers for example, suitable for continuous operation. It can deliver fresh water as well as waste water with a maximum solid size of 0.11 in.

The suction pump has a water level sensor with leaves only a rest water level of 0.08 in. It comes with a 33 ft cable and is mounted together with the sensor in a stainless steel box, which securely prevents the intake of bigger pieces as well as suctioning to the bottom. The standard coupling is a Storz D, but any other coupling is available on request.

Additional Information

Application area	Civil Defence, Field Hospitals, Military, Decontamination and Hazardous Goods Operations, Weatherproof Shelter for Sensitive Equipment and Workshops, United Nations, NGOs/Humanitarian organizations, Associations & Youth groups – tent camps
Delivery height	26.25 ft
Delivery temperature	max. 95°F
Flow rate	max. 10.000 l/h
Driving speed	2.850 1/min
Follow-up time	4 min.
Voltage	230 V/50 Hz
Plug	IP 68
Motor capacity	500 W
Start water level	0.20 in