



# **Double fly tent 300 DV**

### **Product Images**





## **Short Description**

Double fly tents are mainly preferred for youth groups tent camps. They are suitable for longer use even in harsh weather conditions.

#### **Description**

#### **Standard**

Inner tent cabin made of 100% cotton fabric, entrance in front gable, window  $60 \times 40 \text{ cm}$  in the back, top roof with canopy of 2.00 m and closed back gable incl.window  $60 \times 40 \text{ cm}$  with exterior shutter

#### Frame

The frame system consists of anodized aluminium tubes, diameter 40 mm. The connectors and base plates are made of an aluminium alloy.

Wall thickness of 1.5 mm of the material AL Mg 4,5 Mn.

Yield strength: Rp0,2 = 330-340 N/mm2 Ultimate strength: Rm = 350-370 N/mm2

Peg, 20 mm diameter, hot-dip galvanised iron with top forged on, 700 g, 300 mm long

T-peg, galvanised iron, 300 mm long

Peg with hook, galvanised steel, 300 mm long

# **Options**

Tent 200 DV and tent 300 DV can be equipped with sewed in groundsheet at the inner cabin as well as with mosquito nets at windows and entrance.

# **Additional Information**

Application area	Civil Defence, Triage, Field Hospitals, First Aid Posts, Military, Accommodation and Catering, Police/Gendarmerie, Industry and commerce, Weatherproof Shelter for Sensitive Equipment and Workshops, Promotion agencies, Party – Event, Associations & Youth groups – tent camps
Base area	508.06 ft²
Width	19.36 ft
Length	26.25 ft
Eaves height	6.36 ft
Ridge height	9.35 ft