



Pagoda tents PAL 33

Product Images



Short Description

Pagoda tent models are well suited for private occasions, cultural events, sporting events and important occasions for both small and big communities or companies.

Description

Frame

The frame of the pagoda is made of hollow aluminum extrusion profiles. The main frame consists of a 3-channel 63 x 63 mm and the roof diagonals of a 40 x 40 mm profile. All aluminum parts are anodized and maintenance-free. Steel parts, such as base plates, corner and center connectors are hot-dip galvanized according to DIN 50976 and extremely corrosion-resistant. The anchoring is realized by steel anchors.

Tent skin

Roof and side walls are made of high quality both sides PVC-coated polyester fabric with low-wick properties. The outer surface is high glossy embossed; the fabric is flame retardant according to EN 13501-1 B-s3, d0 and has a weight of approx. 670 g/m². As a standard, the roof overhang is straight, but can be cut in sinus curve, if desired. The sidewalls are split into halves by means of a zipper. They can be pushed aside and kept open allowing an open but protected space. Optionally, you can only mount the roof. Several different windows options are available for the sidewalls.

Options

- tensioning bars
- wooden floor
- windows
- sinuous edge border

Additional Information

Application area	Industry and commerce, Promotion agencies, Party – Event
Base area	96.87 ft ²
Width	9.84 ft
Length	9.84 ft
Eaves height	7.54 ft