



## Medical and Accommodation Aluminum Frame Tents - SG 18

### Product Images



### Short Description

SG tents come in 14 standard configurations and 10 different areas of applications. No special tools are required for setup, they are modular and easy to interconnect.

### Description

#### Standard

Tent with entrance in the front gable (toggle closing), window 60 x 40 cm with exterior shutter in back gable, aluminium frame and accessories.

#### Frame

The frame system consists of anodized aluminium tubes, diameter 40 mm. The connectors and base plates are made of an aluminium alloy.

- Wall thickness of 1.5 mm of the material AL Mg 4,5 Mn.
- Yield strength: Rp0,2 = 330-340 N/mm<sup>2</sup>

- Ultimate strength: Rm = 350-370 N/mm<sup>2</sup>

- Peg, 20 mm diameter, hot-dip galvanised iron with top forged on, 700 g, 300 mm long
- T-peg, galvanised iron, 300 mm long
- Peg with hook, galvanised steel, 300 mm long

### Tent skin

LANCO tents are made of LANCO heavy-duty fabric. LANCO-heavy-duty fabric is permeable to the air, rot-resistant, water pressure proof laminated and is extremely tearproof as well as highly protective against UV-rays.

### Fabric:

Twisted cotton-polyester 50%/50% Yarn

### Options:

- Connecting unit, chimney passage, divisibility with loop closing, canopy, partition walls, roll-up facility of one side or one panel
- Window, tent skin
- Window, inner cabin
- Roll-up facility one panel
- Second entrance

### Additional Information

Application area	Military
Base area	190.52 ft <sup>2</sup>
Width	13.39 ft
Length	17.52 ft
Eaves height	5.28 ft
Ridge height	7.38 ft
Packing size	44.00 gal
Weight	138.89 lbs