LANCO
TentTech · DeconTech · FlexTank

Lite Duty Low Pressure Inflatable Shelter ARZ 50

Product Images

Short Description

Quick and easy to (dis)assemble, modular design, multifunctional and interconnectable, ARZ shelters are reliable and highly portable. Base areas range from 65 ft^2 to 650 ft^2.

Description

Frame

Completely inflatable frame made of airtight double-sided PVC-coated polyester fabric (25 oz/yd^2), fastened with Velcro closures to the tent skin and floor. Easy replacement of tent skin, floor and frame. The tents can be set up in 1.5 minutes using the compressed air kit. Depending on tent size, assembly takes 2-4 minutes when using an electric blower. A pressure relief valve prevents excessive pressure in the frame.

Tent skin

Tent skin: One-sided PU coated polyester fabric (7 oz/yd^2); flame retardant, waterproof and mildew resistant design. Tent skin of double-sided PVC coated polyester fabric is also available.

PU-coated fabric is available in 11 different standard colors.

Other colors are available on request. Tent skin of double-sided PVC-coated polyester fabric (14.5 oz/yd²) is also available.

Floor

Floor covering of double-sided PVC-coated polyester fabric (16 oz/yd²). Available with non-slip embossing as an option (25 oz/yd²).

Options and accessories

- Partition walls
- Side windows
- Inner liner
- Fabric according to military standards
- Compressed air kit
- Inflation system
- Ballast tanks
- Lettering/branding
- Lighting
- Air conditioning
- Heating

Additional Information

Application area	Military
Base area	64.00 ft²
Width	11.20 ft
Length	5.70 ft
Eaves height	7.50 ft
Ridge height	9.10 ft
Operating pressure	5.10 psi
Weight	71.00 lbs